PATENT COOPERATION TREATY DCT

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference 509549 DJS	FOR FURTHER ACTION	See Form PCT/IPEA/416							
International application No. PCT/NZ2004/000224	International filing date (day/month/year) 17 September 2004	Priority date (day/month/year) 19 September 2003							
International Patent Classification (IPC) or	International Patent Classification (IPC) or national classification and IPC								
Int. Cl.									
E04D 1/36 (2006.01)									
Applicant									
HAYNES, Andrew, Leo et al									
1. This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36.									
2. This REPORT consists of a total of 4.	sheets, including this cover sheet.								
3. This report is also accompanied by AN	NEXES, comprising:								
a. X (sent to the applicant and to the	e International Bureau) a total of 7 sheets,	as follows:							
sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions).									
sheets which supersede earlier sheets, but which this Authority considers contain an amendment that goes beyond the disclosure in the international application as filed, as indicated in item 4 of Box No. I and the Supplemental Box.									
b. (sent to the International Bureau only) a total of (indicate type and number of electronic carrier(s)), containing a sequence listing and/or table related thereto, in electronic form only, as indicated in the Supplemental Box Relating to Sequence Listing (see Section 802 of the Administrative Instructions).									
4. This report contains indications relatin									
X Box No. I Basis of the repo	rt ·								
Box No. II Priority									
X Box No. III Non-establishme	nt of opinion with regard to novelty, inventi	ve step and industrial applicability							
l									
Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement									
Box No. VI Certain documen		• .							
Box No. VII Certain defects in	Box No. VII Certain defects in the international application								
Box No. VIII Certain observations on the international application									
Date of submission of the demand Date of completion of this report									
18 April 2005	6 December 2005	•							
Name and mailing address of the IPEA/AU	Authorized Officer								
AUSTRALIAN PATENT OFFICE									
PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaustralia.gov.au VINCE BAGUSAUSKAS									
Facsimile No. (02) 6285 3929	Telephone No. (02)	6283 2110							

Form PCT/IPEA/409 (Cover sheet) (April 2005)

INTERNATIONAL PRELIMINARY REPORT ON PATENTARILITY

International application No.

PCT/NZ2004/000224

Bo	c No. I							
1.	Witt	regard to the language, this report is based on:						
	X The international application in the language in which it was filed							
		A translation of the international application into translation furnished for the purposes of: , which is the language of a						
		international search (under Rules 12.3(a) and 23.1 (b))						
		publication of the international application (under Rule 12.4(a))	•					
		international preliminary examination (Rules 55.2(a) and/or 55.3(a))						
2.	With regard to the elements of the international application, this report is based on (replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report):							
•	Ш	the international application as originally filed/furnished						
	X	the description:						
		pages 1-13 as originally filed/furnished						
•		pages* received by this Authority on with the letter of						
	iso	pages* received by this Authority on with the letter of						
	X	the claims:						
		pages as originally filed/furnished						
		pages* as amended (together with any statement) under Article 19 pages* 14-20 received by this Authority on 31 October 2005 with the letter of 26 October 2005						
	X	pages* 14-20 received by this Authority on 31 October 2005 with the letter of 26 October 2005 pages* received by this Authority on with the letter of the drawings:	5					
	兦							
•.		pages 1-17 as originally filed/furnished pages* received by this Authority on with the letter of pages* received by this Authority on with the letter of						
		a sequence listing and/or any related table(s) - see Supplemental Box Relating to Sequence Listing.						
3.	The amendments have resulted in the cancellation of:							
		the description, pages						
		the claims, Nos.						
٠		the drawings, sheets/figs						
		the sequence listing (specify):						
		any table(s) related to the sequence listing (specify):						
	·							
4.		This report has been established as if (some of) the amendments annexed to this report and listed below had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).	; ;					
		the description, pages						
		the claims, Nos.						
·		the drawings, sheets/figs	9					
		the sequence listing (specify):						
		any table(s) related to the sequence listing (specify):						
•	If II	em 4 applies, some or all of those sheets may be marked "superseded."						

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/NZ2004/000224

Box No. V	Reasoned statement un citations and explanati	ider Artic	cle 35(2) with regard to novelty, inventive step or incorting such statement	lustrial applicability;		
1. Statement						
No	velty (N)	Claims	3, 11-14, 16-28, 30, 32-35, 44, 46	YES		
		Claims	1, 2, 4, 6-10, 15, 29, 31, 36-41, 43, 45, 47-53	NO		
Inv	ventive step (IS)	Claims	3, 11-14, 16-28, 30, 32-35, 44, 46	YES		
	•	Claims	1, 2, 4, 6-10, 15, 29, 31, 36-41, 43, 45, 47-53	NO		
Ind	lustrial applicability (IA)	Claims	1-4, 6-41, 43-53	YES		
		Claims		NO		

2. Citations and explanations (Rule 70.7)

The relevant citation from the ISR is

D1) Derwent Abstract 2003-395053/38.

NOVELTY (N) 1, 2, 4, 6-10, 15, 29, 31, 36-41, 43, 45, 47-53

D1) discloses the use of a ridge cap flashing member that is adaptable to be conformed to the roofing material. In particular the surface of the flashing is aid to be "treated to give it a hydrophobic character". To the person skilled in the art this would be understood to include the use of paints. Furthermore the flashing is adhered to the roof material with the use of adhesive bands (15). There is no restriction in the present claim that the ridge overlying region does not have corrugations. Therefore the invention as defined in claims 1 and 39 is considered not to be novel over the prior art.

The features added by the appended claims 2, 4, 6-10, 15, 29, 31, 36-41, 43, 45, 47-53 are also identifiable in the citation.

INVENTIVE STEP (IS) 1, 2, 4, 6-10, 15, 29, 31, 36-41, 43, 45, 47-53

As for Novelty above

PCT/NZ2004/000224 Received 31 October 2005

IAP9 Rec'd PCT/PTO 2 0 MAR 2006

- 14 -

CLAIMS:

- 1. A roof flashing for or suitable for flashing a "ridgeline" as herein defined, said flashing being of multiple materials and being at least in part laminated and comprising or including:
- a) a "ridge" overlying region to overlie the actual or phantom "ridge" to be flashed, the ridge being as herein defined,
 - b) a first flanking region extending from the ridge overlying region, and
 - c) a second flanking region extending from the ridge overlying region,

wherein the ridge overlying region is conformed to a retainable three dimensional form and/or is conformable and can retain to a three dimensional form,

and wherein the first and second flanking regions extend from the ridge overlying region so as to flank the actual or phantom "ridge" to be flashed by the flashing,

- and wherein there is a weathering surface of one or more weathering material(s) and at least one of the flanking regions has at least a partial underlying support of the weathering material(s), and at least one of said flanking regions is at least conformed to a three dimensional form, and is conformable to a retained or retainable three dimensional form or has a distal extremity greater in extent than the proximal extent of that flanking region to said ridge overlying region.
 - 2. A roof flashing as claimed in claim 1 wherein each of the flanking regions has at least a partial underlying support of the weathering material(s).
- A roof flashing as claimed in claims 1 or 2 wherein said first and second
 flanking regions depend from a first zone of articulation immediately adjacent said ridge overlying region.
 - 4. A roof flashing as claimed in any one of claims 1 to 3 wherein the roof flashing includes preferably by removal of a release sheet or release sheets to reveal an adhesive or other tack providing surface to allow at least part of at least

Amended Sheet IPEA/AU

one of the flanking regions to be adhesively attached to a support surface e.g. of a roofing material to be flashed.

- 5. A roof flashing as claimed in any one of claims 1 to 4 wherein in some options one or more materials e.g. as a laminate, provide the ridge overlying region whilst in other forms the ridge overlying region can be at least in part, primarily or wholly of the one or more material(s) providing a weathering surface notwithstanding the fact that the flashing is at least in part laminated (e.g. whether solely in one or both of the flanking regions or otherwise).
- 6. A roof flashing as claimed in any one of claims 1 to 5 wherein the distal ends of one or each of said first and second flanking regions distal from said "ridge" overlying region is conformed into a three dimensional region to allow (by conformity or material thus made available) association with undulating or otherwise three dimensional roofing materials, to be flashed, flanking said "ridge" or "ridgeline".
- 15 7. A roof flashing as claimed in any one of claims 2 to 6 wherein said three dimensional region is at least in part held in its three dimensional form by said partial underlying support.
 - 8. A roof flashing as claimed in any one of claims 2 to 7 wherein said partial underlying support is a conformable yet shape retaining three dimensionally conformed material.
 - 9. A roof flashing as claimed in any one of claims 1 to 8 wherein said three dimensionally conformed material underlies said weathering layer.
 - 10. A roof flashing as claimed in any one of claims 1 to 9 wherein there is sufficient tack retaining adhesive on the non-weathering side of at least part of one or both said first and second flanking regions and/or said three dimensionally to associate said flanking regions to said roofing materials.
 - 11. A roof flashing as claimed in any one of claims 1 to 10 wherein said tack retaining adhesive lies between said weathering layer and said dimensionally conformed material.

Amended Sheet IPEA/AU

20

25

- 12. A roof flashing as claimed in any one of claims 1 to 10 wherein said dimensionally conformed material lies between said weathering layer and said tack retaining adhesive.
- 13. A roof flashing as claimed in any one of claims 1 to 12 wherein said three dimensionally conformed material is a metal.
- 14. A roof flashing as claimed in any one of claims 1 to 13 wherein said metal can be sheet aluminium (and optionally may be wholly or in part be able to be expanded).
- 15. A roof flashing as claimed in any one of claims 1 to 14 wherein said three dimensional region is configured so as to exhibit a substantially sinusoidal section when being viewed in section towards said distal ends.
 - 16. A roof flashing as claimed in any one of claims 1 to 15 wherein said three dimensionally conformed material is a perforate or expanded sheet of a suitable metal.
- 15 17. A roof flashing as claimed in any one of claims 1 to 16 wherein said three dimensionally conformed material is only partially expanded prior to application of said flashing.
 - 18. A roof flashing as claimed in any one of claims 1 to 17 wherein said three dimensional region can expand and contract in directions parallel and transverse
- to said "ridgeline" which said flashing is to flash to further engage and conform to said roofing materials.
 - 19. A roof flashing as claimed in any one of claims 1 to 18 wherein a suitable natural or synthetic rubber material or plastics material provides said exterior flexible weathering surface.
- 25 20. A roof flashing as claimed in claim 19 wherein said suitable natural or synthetic rubber material or plastics material is selected from the Desmopan® range of thermoplastic polyurethane materials.
 - 21. A roof flashing as claimed in any one of claims 1 to 20 wherein said "ridge" overlying region is conformed, as part of said lamination to a substantially rigid section underlying said weathering layer.

Amended Sheet

30

- 22. A roof flashing as claimed in claim 21 wherein said substantially rigid section is of substantially complimentary configuration conforming to said "ridge" beam or beams, or structure defining said "ridgeline".
- 23. A roof flashing as claimed in any one of claims 1 to 22 wherein said flashing has differing degrees of flexibility of the lamination over its cross section.
 - 24. A roof flashing as claimed claim 23 wherein said differing degree of flexibility is at least in part due to differing flexibility of said weathering later.
- 25. A roof flashing as claimed in either of claims 23 or 24 wherein said differing degree of flexibility of said weathering layer is due to differing thickness and/or differing material properties (such as density, flexural strength, Shore hardness etc) of said weathering layer.
 - 26. A roof flashing as claimed in any one of claims 21 to 25 wherein said weathering layer over said rigid section is between 100 and 600 microns thick.
- 15 27. A roof flashing as claimed in any one of claims 21 to 26 wherein said weathering layer over said rigid section is 200 microns thick.
 - 28. A roof flashing as claimed in any one of claims 1 to 27 wherein said three dimensionally conformed material is mould embedded at least in part in another material, said another material being flexible but not necessarily being said flexible material(s) providing the exterior weathering surface.
 - 29. A roof flashing as claimed in any one of claims 4 to 28 wherein a release sheet is associated with said tack retaining adhesive.
 - 30. A roof flashing as claimed in any one of claims 1 to 29 wherein said "ridge" overlying region includes a number of openings therethrough to allow penetrative fixers to affix the same to a "ridge" beam or beams.
 - 31. A roof flashing as claimed in any one of claims 1 to 30 wherein said flashing is to underlie a ridge cap or ridge tile.
 - 32. A roof flashing as claimed in any one of claims 1 to 31 wherein said flashing has, at said distal ends further extensions ("flank returns") which have a third zone of articulation from said distal end to be articulated to engage with the

20

25

30

under side of said ridge capping(s) or tile(s) to form a further water and weather proofing of said ridge.

- 33. A roof flashing as claimed in claim 32 wherein said zone of articulation runs parallel to said ridge overlying region.
- 5 34. A roof flashing as claimed in either claim 32 or 33 wherein said flank returns are separable into portions by lines of separation running substantially perpendicular to said line of articulation.
 - 35. A roof flashing as claimed in any one of claims 32 to 34 wherein said flank returns further have zones of adhesion to engage with the underside of said ridge capping(s) or tile(s).
 - 36. A roof flashing as claimed in any one of claims 1 to 35 wherein said flashing may form the ridgeline without reliance upon a ridge cap or ridge tile.
 - 37. A roof flashing as claimed in any one of claims 1 to 36 wherein said flashing is coloured to match the roofing material or tiles to which it is applied.
- 15 38. A roof flashing as claimed in any one of claims 1 to 37 wherein said flashing may be coloured in a form as desired by the end user.
 - 39. A method of flashing a roof with a flashing as herein before described, wherein the ridge overlying region is applied to an actual or phantom "ridge" to be flashed,
- first and second flanking regions extending from said ridge overlying region are located to lie upon and confirm to roofing material(s) either side of said ridge with at least one of the flanking regions is at least conformed to a three dimensional form, and is conformable to a retained or retainable three dimensional form or has a distal extremity greater in extent than the proximal extent of that flanking region to said ridge overlying region to conform with said roofing material(s) and thus to form with said roofing material(s) a continuous weathering surface.
 - 40. A method as claimed in claim 39 wherein each of the flanking regions has at least a partial underlying support of the weathering material(s).

- 51. A flashing as herein described when of a form and/or structure substantially as hereinbefore described with reference to any one or more of the accompany drawings.
- 52. The use or methods of use of a flashing or flashing structure of any of the kinds as herein described.
 - 53. A structure flashed by a flashing or flashing structure of any one of claims as herein described.